



**Australian  
Security Fencing**

*Protecting your interests*

## **PRODUCT SPECIFICATION – “CLG200” - CANTILEVER GATE**

### **PROPRIETARY SPECIFICATION**

“CLG200” Cantilever Gate as manufactured by Australian Security Fencing

#### **SUB FRAME**

Gate structure shall be manufactured using pre-galvanised steel SHS / RHS sections

#### **GATE INFILL**

Infill shall be typically vertical bar utilising 25mm SHS.

#### **TRACK DETAIL**

100mm Cantilever Track

#### **AUTOMATION**

Automation is provided via high duty electro-mechanical gate operator.

Australian Security Fencing Safety supplied as standard with in built obstacle detection, dual height and dual side photo-electrical beams, flashing light and warning sign.

#### **FINISH OPTIONS:**

- Galvabond steel (standard)
- Dulux Duralloy or Interpon D100 powdercoat finish
- Electro – static twin coat wet sprayed paint.

#### **SPECIAL NOTES:**

- The power supply required for the motor is either:
  - Single phase hard wired (10 amp), located within one metre of the motor.
  - Low voltage 24v wired supply, within one metre of the motor.
  - 24v High efficiency solar power.

Australian Security Fencing has continuous program of product development, and reserve the right to change specifications at any time without notice