

## **PRODUCT SPECIFICATION – SHORT BARB RAZOR TAPE**

### **PROPRIETARY SPECIFICATION**

SHORT BARB RAZOR TAPE as supplied by Australian Security Fencing

#### **Galvanized Blade Strip**

- Galvabond G2 0.55mm Thick
- Coating Class Z275
- Hardness HR30T 50-60 (typical)
- Surface Finish: Spangled
- Surface Treatment: Chromated
- Australian Standard AS 1397

#### **Tape Configuration**

- Clusters of barbs at 25mm(+/-1mm) centres
- Each barb 10mm (approx) long with needle sharp points.
- Width of barbed tape: 14mm. Hard-Drawn Galvanized Spring Steel Wire Range 2
- Standard: AS 1472/1979 • Diameter: 2.5mm (+/-0.02)
- Tensile Strength: 1730-1950 MPa
- Galvanizing: Galvanized 125g/m<sup>2</sup> (min)
- Class WO5 AS4534-1998.

#### **Concertina Clips**

- Galvabond G2 1.6mm Thick x 9.7mm wide
- Coating Class Z275
- Hardness HR30T 50-60 (typical)
- Surface Finish: Spangled
- Surface Treatment: Chromated
- Australian Standard AS 1397

Australian Security Fencing has continuous program of product development, and reserve the right to change specifications at any time without notice